

# Fox River cleanup



James Hahnenberg


Sediment Remediation Course  
Chicago  
November 30, 2005



# **Fox River**

- 1. The problem**
  
- 2. Decisions (i.e., RODs)**
  
- 3. Work**
  - a. Dredging projects and lessons**
  - b. Contractors advice**

# Fox River PCBs: from papermills



Modified from Green  
Bay Press Gazette



Black Crappie



Bluegill



Brown Trout



Carp



Channel Catfish



Chinook Salmon



Northern Pike



Rock Bass



Rainbow Trout



Smallmouth Bass



Splake



Sturgeon



Walleye



White Bass



White Fish



White Sucker




White Perch



Yellow Perch


# PCB fish

## consumption advisories




# Fox River decisions

**ROD #1**  
December 2002




# Cleanup level & time to Acceptable Fish Tissue Levels\* for OU 1



\* For unlimited fish consumption for young-of-year fish

# Fox River PCB cleanup goals



\*Surface Weighted Average Concentration

# Dredging versus Capping

	Dredging	Capping
Short-term releases	Small	Smaller
Contaminant disposition	Mostly removed to landfill	Contained* in river
Habitat	Altered/disrupted (eventual recovery)	Permanent change

**Preferred**



**\*Assumes long-term stability**

# Dredging versus Capping

	Dredging	Capping
Construction impacts	Larger “footprint”	Smaller “footprint”
	Some noise, traffic, odors	Less noise, traffic, odors
Monitoring & maintenance	Limited monitoring	More monitoring & institutional controls
Cost	High	Moderate
Water depth	Increased	Decreased

**Preferred**



# Post-dredging residuals


Project	Contaminant	Average % Reduction
Grasse River	PCBs	79*
GM Massena	PCBs	99*
Cumberland Bay	PCBs	97*
New Bedford	PCBs	97*
Marathon Battery	Cadmium	92*
Lake Jarnsjon	PCBs	99*
<b>SMU 56/57 (Fox)</b>	PCBs	96
<b>AVERAGE</b>		94

\* From: Hudson River Record of Decision, Responsiveness Summary White Paper (312663), Post-Dredging PCB Residuals

# Remedy Decisions (2003-2004)


Total cost:  
\$400 million


- Dredging: \$350 million
- MNR \$50 million



# OU 1 and OU 2


## December 2002 ROD





# OU 1

1. Dredge 800,000 cubic yards with PCBs more than 1 ppm
2. Mechanical dewatering
3. Trucking
4. Disposal
  - Capping contingency




# Capping: possible dredging supplement

1. Post-capping water depth 3-feet+
2. Not in navigation channel
3. Avoid pipelines, utilities, etc.
4. PCBs less than 50 ppm


# OU 2 decision

- Natural Recovery (i.e., burial, breakdown, dilution)

- Monitoring to track “recovery”



# PCBs by river segment (pounds)




# Fox River PCB concentrations

		Operable Unit			
Media		1	2	3	4
Sediments (ppm)	Average <sup>1</sup>	15	5	5	20
	Surface average	3.7	0.2	2.1	3.0
Water (ppt)	Average	28	17	41	61

<sup>1</sup> All depths

Sediment goal: 0.25 ppm

# Lower Fox River profile (side view)




# Bedrock under contaminated sediments



Can't “over-dredge” remaining thin layer

Photo courtesy of WDNR



# Difficult conditions for dredging

Project	Site conditions		
	Underlying bedrock	Debris	Wood
Manistique	x	x	x
Grasse River			x
Deposit N	x		




**Wood debris  
Manistique River, MI**

# Rock debris

## Grasse River, NY



# Monitored Natural Recovery for OU 2


A scenic view of a river flowing through a forested area. In the background, a large, modern white building with a flat roof is visible on a hillside. The river is rocky and shallow in the foreground, with a few people standing on the right bank. The surrounding area is densely forested with green trees.

1. Relatively small PCB mass
2. Lower PCB concentrations
3. Dredging *not* selected
  - a. Bedrock
  - b. Access

# OU 3, OU 4 Decision

1. Dredge 6.5 million cubic yards with PCBs greater than 1 ppm
2. Pipeline to settling basins and landfill
3. Passive Dewatering
4. Landfill disposal

- **Capping Contingency**



# OU 5 Decision (Green Bay)

- Monitored Natural Recovery
- More modeling
- Dredging near river mouth



# Green Bay and Fox River contamination levels

Media		Fox River	Green Bay
<b>Sediments (ppm)</b>	Mean <sup>1</sup>	11	0.3
	SWAC <sup>2</sup>	2.6	0.2
Water (ppt)	Mean	37	7
Walleye (ppm)	Mean	1.4	1.6

Sediment goal: 0.25 ppm

<sup>1</sup> All sediments, all depths

<sup>2</sup> Surface Weighted Average Concentration

# **Green Bay decision rationale**

- Large volume – disposal “impracticable”
- Relatively low concentrations
- Removal of highest concentrations  
near river mouth


# **Remedy considerations**

## **Summary**

- **Risk reduction: concentrations and mass**
- **Results on Fox River and other dredging projects**
- **Site conditions (e.g. bedrock)**

# Fox River

## Dredging projects



# Fox River dredging projects


Downstream



	OU 1	Deposit N	SMU 56/57
<b>Years</b>	<b>2004-2010</b>	<b>1998-1999</b>	<b>1999-2000</b>
<b>Volume - CY</b>	<b>800,000</b>	<b>8,000</b>	<b>80,000</b>
<b>Costs</b>	<b>\$60 million (estimate)</b>	<b>\$4 million</b>	<b>\$17 million</b>
<b>Cost/CY</b>	<b>\$75</b>	<b>\$500</b>	<b>\$340</b>

# Fox River SMU 56/57

## LOCATION MAP




Hydraulic dredge

Dredge slurry pipeline →

Silt curtains →

# SMU 56/57

## Process schematic



From: Ft. James Corp., 2001 Final Report,  
2000 Sediment Management Unit 56/57 Project




**Sand removal tank and debris screen**




**Storage tanks**



**Hydrocyclones**



**Polymer & press feed pumps**



**Plate and frame Presses**

**SMU 56/57  
Dewatering**

# OBJECTIVES ACHIEVED



- Met cleanup standards
- 2000: removed 50,000 cubic yards (670 lbs PCBs)\*
- Completed on schedule (69 days)



\*Total removal for 1999-2000  
dredging: 80,000 cubic yards  
and 2,111 pounds PCBs

# Things that worked

1. Clear goals and flexibility in *how* to achieve
2. Production objectives & schedule



From: Ft. James, et al, Final Report,  
SMU 56/57, January 2001.

# Things that worked

## 3. Daily meeting with company, agencies and contractors

- a. Issue identification
- b. Problem resolution



## 3. One contractor for most work

- a. Equipment flexibility
- b. Proven dredging experience

# Things that worked

## 5. Over-design treatment capacity relative to dredge



## 6. Extra dredges



# **Things that didn't work (1999 dredging)**

- 1. No “meeting of the minds” between agency and companies doing work**
- 2. Multiple contractors**

# Fox River

## OU 1 dredging




 **DELORME**

Data use subject to license.  
© 2004 DeLorme, Topo USA® 5.0.  
[www.delorme.com](http://www.delorme.com)

MN (3.2° W)

mi  
0 2 4 6 8 10 12  
Data Zoom 8-3



# OU 1 dredging

- 1. Dredge sediments (800,000 cubic yards)**
- 2. Dewater sediment**
- 3. Treat dredge water**
- 4. Dispose at landfill**

# Hydraulic Dredge

- “8-inch”
- Swinging ladder
- Spud barge
- 



Photo courtesy of  
WDNR

2005

**2 hydraulic dredges**  
**(no silt curtains)**



**Photo courtesy of WDNR**

# Cutterhead cleaning



Photo courtesy of Boldt

# Sediment processing facility - 2005





Photo courtesy of Little  
Lake Cleanup Team

# **Geotubes for dewatering dredge slurry**

- **Gravity drainage – collect and treat water**
- **Reduces overhead costs**
- **“Decouples” dredging & dewatering**
- **Less potential air release**

# Storage pad for geotextile tubes



A large, dark, corrugated industrial pipe lies on a gravel surface. Water is dripping from the bottom edge of the pipe, creating a small pool on the ground. The pipe is part of a larger system, with other pipes and structures visible in the background.

**Solids captured  
& water drains  
out**

# Geotube dewatering assistance



Photo courtesy of Boldt

# Geotube dewatering assistance



Photo courtesy of Boldt

# Geotubes: they're big



- 200 feet long
- 80 foot circumference
- Contains 1600 cubic yards

# Stacked tubes




From: Little Lake Cleanup Team

11 12:37PM

# Mechanical dewatering schematic

Geotubes  
replace



From: Ft. James Corp., 2001 Final Report,  
2000 Sediment Management Unit 56/57 Project

# Geotube problems

1. Breakage
2. “Blinding” of pad
3. Space
4. “Workability” issues –  
increase disposal costs

# Tube break



# Possible causes for geotube breaks

- Added ports
- Hole burned by vibration
- Layout and stacking
- Overfilling bag

# Pad blinding





Pad blinding

# Water treatment



- Carbon filters
- Air flotation
- Sand/gravel filters

From: WDNR webpage

# Water treatment plant operating panel

7/27/2005

Lower Fox River OU1 Remedial Action

4:49:48 PM

INFLUENT FLOW RATE (GPM) 1788  
EFFLUENT FLOW RATE (GPM) 1189

MAIN SCREEN

ALARM HORN  
SILENCE

EFFLUENT  
FLOW RATE  
1189 GPM

TURBIDITY  
0.0 NTU

CONTROL SETPOINTS  
ALARM SETPOINTS

SLUDGE  
TANK  
LEVEL  
50 FEET



CARRIAGE  
WET WELL  
LEVEL  
6.7 FEET

EFFLUENT FLOW TOTAL (GALx1000)  
TODAY 21948  
YESTERDAY 120876

RESET


DREDGING  
FLOW RATE  
1953 GPM

GAC FILTERS  
DIFFERENTIAL PRESSURE  
#1 7.2 LBS  
#2 6.1 LBS  
#3 5.0 LBS  
#4 6.9 LBS  
#5 2.8 LBS  
#6 2.0 LBS

FLOW RATE  
#1 & #2 448 GPM  
#3 & #4 310 GPM  
#5 & #6 748 GPM

CREATE DAILY  
REPORT

Alarm History Viewer



CARRIAGE  
WATER  
FLOW RATE  
1788 GPM  
TURBIDITY  
0.0 NTU  
DREDGE  
SLURRY DENSITY  
65.24 g/cm  
STREAMING  
CURRENT  
-11.0 SCU

Ack	Date In	Time In	Tagname	Description	Status	Value

Photo courtesy of Boldt

# Loading



## Landfill disposal\*



\* Engineered for  
contaminant containment

From: Little Lake Cleanup Team

# Things that worked

1. Geotubes

2. Multiple contractors

3. Property purchase

# Things that worked

4. Full scale test in 2004
5. Agency flexibility in *how* to achieve cleanup standards
6. Cooperative relationship

# Fox River dredging projects

	OU 1	SMU 56/57
Contractors	Multiple	One
Dewatering	Geotubes	Plate and frame presses
Dredges	Two operating	One operating & backup

# THE POST-CRESCENT

## LOCAL NEWS

Posted Sept. 24, 2004

### PCB dredging a smooth operation

Little Lake Butte des Morts cleanup surpasses expectations

By Duke Behnke

*Post-Crescent staff writer*

TOWN OF MENASHA — Engineers and contractors are all smiles three weeks into the six-year, \$62 million cleanup of PCBs from Little Lake Butte des Morts.

A high-tech hydraulic dredge has been removing PCB-contaminated



#### Clean up at a glance

**Who:** The Little Lake Cleanup Team consists of GW Partners and its contractors. Representatives can be reached at 920-912-5065 or by e-mail at [littlelakecleanup@execpc.com](mailto:littlelakecleanup@execpc.com).

# Lessons from contractors:

- Enough data & the “right” data
- Practical cleanup objectives

....gives better bids  
(i.e. lower cost)

## Detailed Evaluation of Alternatives Report

### Lower Fox River and Green Bay Wisconsin

Prepared by:

The RETEC Group, Inc.  
22 N. Carroll Street, Suite #370  
Madison, Wisconsin 53703

RETEC Project Number: WISCI-15933-121

Prepared for:

Wisconsin Department of Natural Resources  
101 S. Webster Street  
Madison, Wisconsin 53702

and

United States Environmental Protection Agency  
Region 5  
77 W. Jackson Boulevard  
Chicago, Illinois 60604

Senior Authors:

Grant Hainsworth, P.E. Project Engineer  
Greg Hartman, P.E., Dalton, Olmsted & Fuglevand, Ltd.  
Dr. Michael Palermo, P.E., Corps  
Bob Paulson, Senior Environmental Scientist  
Frederick M. Swed, Jr. P.E., Senior Engineer  
Tim Thompson, Senior Environmental Scientist

Technical Review by:


  
Tom Kreutz, P.E., Senior Engineer

November 2003

# Sampling lessons

- RI Cores were tied to water bottom (mistake)
- Dredgers need elevation
- Get engineering data early




## Elevation datum



# Sampling lessons (continued)

- Get engineering data early
- Money for lots of data is “money well spent” (to reduce dredging footprint)

# Pre-design sampling



Legend

- 2005 Site
- 2004 Site
- Overall Site Boundaries
- Demol
- Federal Navigation Channel
- 2009 Area Previously Remediated

1509

Figure 2-1  
Remedial Design Sediment  
Core Location Map  
Operable Units 2 to 5  
Lower Fox River

ANCHOR  
SHAW

# Pre-design sampling

	OU 1 (upstream)	OU 2- 5 (downstream)
<b>River length (miles)</b>	6	12
<b>Horizontal sample density</b>	1 sample every 1 – 2 acres	1 sample every 1.5 – 6 acres
<b>Vertical interval</b>	<b>every 6 inches</b>	
<b>Number of samples</b>	<b>PCBs</b>	5800
	<b>Geotechnical</b>	550
		9700
		780



**Photo from Ann Schell**